

# Specifications

## ■ Main Components

Overall length	91.7 in (2,330 mm)
Overall width	37.8 in (960 mm)
Overall height	<b>CRF1100A/D</b> 54.9 in (1,395 mm)
	<b>CRF1100A4/D4</b> 61.4 in (1,560 mm)
Wheelbase	62.0 in (1,575 mm)
Minimum ground clearance	9.8 in (250 mm)
Caster angle	27.5°
Trail	4.4 in (113 mm)
Curb weight	<b>CRF1100A</b> 498 lb (226 kg)
	<b>CRF1100D</b> 520 lb (236 kg)
	<b>CRF1100A4</b> 529 lb (240 kg)
	<b>CRF1100D4</b> 551 lb (250 kg)

Maximum weight capacity <sup>*1</sup>	<b>CRF1100A/D</b> 454 lb (206 kg)
	<b>CRF1100A4/D4</b> 450 lb (204 kg)
Maximum weight on rear carrier	<b>CRF1100A4/D4</b> 22 lb (10 kg)
	Rider and 1 passenger
Passenger capacity	8.5 ft (2.6 m)
Minimum turning radius	66.1 cu-in (1,084 cm <sup>3</sup> )
Displacement	3.62 x 3.21 in (92.0 x 81.5 mm)
Bore x stroke	10.1:1
Compression ratio	Unleaded gasoline
Fuel	Recommended: 86 PON or higher
	<b>CRF1100A/D</b> 4.97 US gal (18.8 L)
Tank capacity	<b>CRF1100A4/D4</b> 6.55 US gal (24.8 L)

\*1 : Including rider, passenger, all luggage, and accessories