

Specifications

■ Main Components

Overall length	65.0 in (1,650 mm)
Overall width	26.4 in (670 mm)
Overall height	40.7 in (1,035 mm)
Wheelbase	46.5 in (1,180 mm)
Minimum ground clearance	4.1 in (105 mm)
Caster angle	26.5°
Trail	3.0 in (75 mm)
Curb weight	179 lb (81 kg)
Maximum weight capacity *1	269 lb (122 kg)
Maximum luggage weight *2	Center compartment 22 lb (10 kg)
	Fairing pocket 1 lb (0.5 kg)
	Hook 1 lb (0.5 kg)
	Inner rack 1 lb (0.5 kg)
Passenger capacity	Rider only. No passengers
Minimum turning radius	5.84 ft (1.78 m)

*1 : Including rider, all luggage, and accessories.

*2 : Includes the weight of the luggage and added accessories.

Displacement *1	3.0 cu-in (49 cm ³)
Bore x stroke	1.56 x 1.59 in (39.5 x 40.3 mm)
Compression ratio	12.0:1
Fuel	Unleaded gasoline Recommended: 86 PON or higher
Tank capacity	1.19 US gal (4.5 L)
Battery	GTZ5S 12 V-3.5 Ah (10 HR)
Primary reduction	V-matic (2.85:1 - 0.86:1)
Final reduction	12.321

*1 : Displacement less than 9.2 cu-in (150 cm³) may have highway operating restrictions depending on state laws.